

Kompressor-Anlagen

BOGE Typ	Hubvolumenstrom (Ansaugleistung)		Volumenstrom (Liefermenge nach VDMA 4362)		Kompressor- Drehzahl min ⁻¹	Zylinder- zahl	Motor		Maße B x T x H ca. mm	Gewicht ca. kg
	l/min	cfm	l/min	cfm			kW	PS		
10 bar superschallgedämmt										
SC 6	710	25	542	20	730	2	4	5,5	830x1120x1570	341
SC 8	970	35	734	26	1010	2	5,5	7,5	830x1120x1570	363
SC 10	1330	47	1009	36	920	3	7,5	10	830x1120x1570	389
SC 15	2030	72	1508	54	1050	4	11	15	830x1120x1570	453
SC 20	2600	92	1913	68	1350	4	15	20	830x1120x1570	463
15 bar superschallgedämmt										
SC 3	320	12	283	10	650	2	2,2	3	830x1120x1570	337
SC 4	450	16	394	14	920	2	3	4	830x1120x1570	343
SC 6	610	22	541	19	625	3	4	5,5	830x1120x1570	368
SC 8	800	29	693	25	830	3	5,5	7,5	830x1120x1570	390
SC 10	1100	39	928	33	1130	3	7,5	10	830x1120x1570	397
SC 15	1640	58	1319	47	1130	4	11	15	830x1120x1570	463
SC 20	2030	72	1615	58	1400	4	15	20	830x1120x1570	473

Emissions-Schalldruckpegel nach PN8NTC2.3 ab **60 dB(A)**