

BOGE Typ	Höchst- druck		Effektive Liefermenge*		Motor- leistung		Maße schallgedämmt	Maße superschallgedämmt/ mit Radiallüfter	Druck- luft- aus- tritt	Gewicht schallged./ m. Radiallüfter kg	Gewicht super- schallged. kg
	bar	psig	m ³ /min	cfm	kW	PS	B x T x H in mm	B x T x H in mm			
SLF 221	8	115	6,46-28,21	228- 996	160	220	3145 x 1910 x 2145	3145 x 1910 x 2645	DN 100	4500/ –	4600
	10	150	6,18-25,06	218- 885	160	220	3145 x 1910 x 2145	3145 x 1910 x 2645	DN 100	4500/ –	4600
	13	190	5,46-20,36	193- 719	160	220	3145 x 1910 x 2145	3145 x 1910 x 2645	DN 100	4500/ –	4600
SLF 271	8	115	6,46-34,70	228-1225	200	270	3145 x 1910 x 2145	3145 x 1910 x 2645	DN 100	4700/ –	4800
	10	150	6,18-30,50	218-1077	200	270	3145 x 1910 x 2145	3145 x 1910 x 2645	DN 100	4700/ –	4800
	13	190	5,46-24,73	193- 873	200	270	3145 x 1910 x 2145	3145 x 1910 x 2645	DN 100	4700/ –	4800